



AN INDUSTRIAL OILS

The AN range of industrial lubricants are general-purpose circulating oils, designed for systems where the lubricant is continuously pumped, filtered, and reused. They provide stable lubrication, cooling, and protection in industrial machinery that operates for long periods under moderate loads and temperatures.

KEY PERFORMANCE ADVANTAGES

- Excellent oxidation and thermal stability
- Reliable rust and corrosion protection
- Good water separation (demulsibility)
- Low foaming tendency for smooth circulation

Available grades: 22, 32, 46, 68, 100,150

Packaging : 18L, 205L

PRODUCT DATASHEET - TYPICAL VALUES

Index	Testing Method	Viscosity Grade					
		22	32	46	68	100	150
Specific gravity at 15 °C	EN ISO 3675	0.87	0.87	0.87	0.88	0.88	0.89
Kinematic viscosity 40°C , mm/s ²	EN ISO 3104	22	32	46	68	100	150
Viscosity index	ISO 2909	-	90	90	90	90	90
Flash point, °C	EN ISO 2592	200	200	200	215	225	230
Pour point, °C	ISO 3016	-7	-7	-7	-5	-5	-3
Acid number, mgKOH/g	ASTM D 974	0.1	0.1	0.2	0.2	0.25	0.25